

Advanced IP Phone with 3 lines & HD voice

- TI TITAN chipset and TI voice engine
- 3 VoIP accounts, 132x64 graphic LCD
- HD Voice: HD Codec, HD speaker, HD handset
- BLF, XML Browser, Hot-desking, OpenVPN
- 2xLAN, PoE, Headset, Expansion module



Yealink SIP-T26P is an advanced IP phone which designed for maximum productivity and efficiency in the everyday business environment. It is equipped with the TI TITAN chipset, offers high definition voice quality through TI voice engine, HD handset, HD speaker and HD codec (G.722).

Built-in 10 DSS keys for programmed as the IP-PBX features like BLF/BLA, intercom, call pickup, XML browser, Hot desking, etc. Six navigation keys and four soft keys help you to use the phone easily.

Ten dedicated functional keys provide you with direct access to the functions for audio and call control. Moreover, SIP-T26P has the rich external interfaces including 2xLAN, PoE, headset and expansion module ports, supports 802.1x, Open VPN, etc security standards.

Phone Features

3 VoIP accounts, Hotline, Emergency call
 Call hold, Call waiting, Call forward, Call return
 Call transfer (blind/semi-attended/attended)
 Caller ID display, Redial, Mute, DND
 Auto-answer, 3-way conferencing
 Speed dial, SMS, Voicemail
 Message Waiting Indication (MWI) LED
 Tone scheme, Volume control
 Direct IP call without SIP proxy Ring
 tone selection/import/delete
 Phonebook (300 entries), Black list
 Call history: dialed/received/missed/forwarded
 Menu-driven user interface
 Localized language and input method
 Soft keys programmable
 Supports up to 6 expansion modules(EXP38 and EXP39)
 Supports Wireless Headset Adapter(EHS36)

Advanced Features

XML phonebook search/import
 LDAP phonebook
 XML Browser, Hot-desking

IP PBX System Integration

Busy lamp field (BLF), BLF list
 Bridged line appearance (BLA)
 DND&Forward synchronization
 Intercom, Paging, Music on hold
 Call park, Call pickup
 Call recording, Call completion
 Group listening, Group pickup
 Anonymous call, Anonymous call rejection
 Network conference
 Distinctive ringtone
 Dial Plan, Dial-now

Codecs and Voice Features

Wideband codec: G.722
 Narrowband codec: G.711μ/A, G.723.1
 G.726, G.729AB
 VAD, CNG, AEC, PLC, AJB, AGC
 Full-duplex speakerphone with AEC

Network Features

SIP v1 (RFC2543), v2 (RFC3261)
 DNS SRV (RFC3263)
 Redundant server support
 NAT Traversal: STUN mode
 DTMF: In-Band, RFC2833, SIP Info
 Proxy mode and peer-to-peer SIP link mode
 IP Assignment: Static/DHCP/PPPoE
 Bridge/router mode for PC port
 TFTP/DHCP/PPPoE client
 Telnet/HTTP/HTTPS server
 DNS client, NAT/DHCP server
 Logout

Management

Auto-provision via FTP/TFTP/HTTP/HTTPS
 Auto-provision with PnP
 SNMP V1/2 optional, TR069 optional
 Configuration: browser/phone/auto-provision
 Factory configuration customized
 Trace package and system log export

Security

Open VPN, 802.1x, VLAN QoS (802.1pq)
 Transport Layer Security (TLS)
 HTTPS (server/client), SRTP (RFC3711)
 Digest authentication using MD5/MD5-sess
 Secure configuration file via AES encryption
 Phone lock for personal privacy protection
 Admin/VAR/User 3-level configuration mode

Physical Features

TI TITAN chipset
 132x64 graphic LCD
 45 keys including 13 programmable keys
 1xRJ9 (4P4C) handset port
 1xRJ9 (4P4C) headset port
 2xRJ45 10/100M Ethernet ports
 1XRJ12 (6P6C) EXT port
 Power adapter: AC 100~240V input and DC 5V/1.2A output
 Power over Ethernet (IEEE 802.3af)
 Power consumption: 1.6-2.6W
 Net weight: 1.05KG
 Dimension: 273x204x42MM
 Operating humidity: 10~95%
 Storage temperature: up to 60°C

Package Features

Qty/CTN: 5 PCS
 N.W/CTN: 8.065KG G.W/CTN:
 8.915KG Measurement:
 0.062CMB Carton Meas:
 580x320x300MM

Certifications

